



January 10, 2025

**NOTICE OF AWARD**

**VARIANCE TRADING CORPORATION**

AGG-CT II Bldg., V. Luna Road Corner Matapat Street,  
Barangay Pinyahan, District 4, Quezon City  
Tel. No.: 8983-4616; 8983-1973  
Email: kathrinafurigay@variancetradingcorporation.com

Dear Sir/Madam,

Please be advised that as a result of **Public Bidding** conducted by National Center for Mental Health for the **Supply, Delivery, Installation, Testing and Commissioning of Brand-New Operating Room Table for Pavilion 7 – General Hospital CY 2024**, and is hereby **awarded** to your company the following:

ITEM CODE	ITEM DESCRIPTION	QTY	UOM	UNIT PRICE	TOTAL PRICE
OR-01-2024	<p><b>Supply, Delivery, Installation, Testing and Commissioning of Brand-New Operating Room Table for Pavilion 7 – General Hospital CY 2024</b></p> <p><b>Brand: Mindray</b> <b>Model: Hybase V8</b> <b>Country of Origin: China</b></p> <p><b>OPERATING ROOM TABLE FOR VARIOUS SURGICAL DISCIPLINE WITH ORTHOPEDIC TRACTION DEVICE</b></p> <p><b>GENERAL DESCRIPTION</b></p> <ul style="list-style-type: none"> <li>• Safe working load of at least 400kg guaranteeing highest safety and stability.</li> <li>• All position at least 250kg loading weight.</li> <li>• The table top should be radiolucent material &amp; X-Ray access</li> <li>• With Modular design tabletop that enables it to be tailored for various surgical discipline needs.</li> <li>• Easy to change or adjust table components module.</li> </ul>	1	unit	₱ 6,410,000.00	₱ 6,410,000.00

*"There is no Health without Mental Health"*

sent dated 01/12



	<ul style="list-style-type: none"> <li>• Equip with system that shall recognize the type of the table component and match the anti-collision data automatically. (Optional)</li> <li>• Equip with warning/notification technology to prevent excessive angle movement in the Trendelenburg and reverse Trendelenburg positions.</li> <li>• The table pad should be thick if (single) or double layered and not soft but can be molded by the figure of the patient to deliver even counterforce and reduce the possibility of ulcer, and it should be water-proof and anti-static material and can be washed by water directly; each joint should be sealed by ultrasonic not glue and sewing.</li> <li>• The thickness of the mattress should be at least 75mm -85mm multilayer decompression pad with waterproof and seamless design</li> <li>• With dual-joint leg plate and dual-joint head plate.</li> <li>• With flat stainless-steel design material as the cover of the table base not metal to avoid the potential shocking by the current.</li> <li>• It shall be battery powered and electric /electro-hydraulic or electro mechanical operating table with battery inside the table, which can work at least 50-80 operations for two weeks and the battery should be standard configuration.</li> <li>• Capable of interchangeable for the leg plates and head rest for normal position and reverse position</li> <li>• With electric longitudinal shift function of at least 330mm for free access to C-arm.</li> <li>• With bottom base height not less than 130mm</li> <li>• Equip with table memory position technology or it's equivalent (Optional).</li> <li>• Equip with electro-hydraulic or electro mechanical system that includes table up and down, back up and down, turn left and right, Trendelenburg and reverse Trendelenburg, leg plate up &amp; down, which shall be controlled by hand control panel and/or remote control.</li> <li>• Support zero "0" position by one electric button.</li> <li>• Support powered body elevator and flex position can reduce the pressure injury and expose the kidney area completely</li> <li>• With 4 double-swivel castors that are operated electrically and hand control for easy table movement.</li> </ul>				
--	--	--	--	--	--

- With wired and wireless hand controller with at least 3.5" color LCD that will show the information on the display, such as movements, battery, brake, anti-collision information, etc.
- The remote hand control shall be with the backlight for operating in a dark environment
- With electric/manual brake

**TECHNICAL SPECIFICATION**

**Basic Information**

- Length of the table (main unit) at least 870 mm
- Width of the table with rails at least 570 mm.

**Electric Function**

- The lowest position at 660 mm or lower
- The highest position at least 1000 mm to 1100 mm
- Longitudinal shift at least 330 mm
- Tilting position for both left and right must be minimum of 25°
- Trendelenburg position and Reverse Trendelenburg position must be minimum of 30°
- Back plate up position at least 75°
- Back plate down position at least 40°
- Flex position  $\geq 220^\circ$
- Re-flex position  $\geq 110^\circ$
- Leg plate up at least 20°
- Leg plate down at least 90°

**Mechanical Function**

- Head plate up  $\geq 45^\circ$
- Head plate down  $> 80^\circ$

**ACCESSORIES**

**Standard:**

- One pair arm board with cushion and clamp
- One piece anesthesia screen I shaped with clamp

**ORTHOPEDIC TRACTION:**

ORTHOPEDIC TRACTION DEVICE  
(COMFORT)

<p><b>SPECIFICATION:</b></p> <p><b>Swivel Bar</b></p> <ul style="list-style-type: none"> <li>• Made of stainless steel or carbon fiber</li> <li>• Length at least 1365 – 1660 mm</li> </ul> <p><b>Counter Traction Post</b></p> <ul style="list-style-type: none"> <li>• Length – at least 340mm-380mm;</li> <li>• Diameter - at least 95mm-105mm</li> </ul> <p><b>Counter Traction</b></p> <ul style="list-style-type: none"> <li>• Material: Made of polyoxymethylene</li> </ul> <p><b>Pelvis Plate</b></p> <ul style="list-style-type: none"> <li>• Material: Made of Compact Laminate or Carbon Fiber</li> </ul> <p><b>Swivel Bar</b></p> <ul style="list-style-type: none"> <li>• Horizontal rotate range – 130 degrees to 220 degrees</li> </ul> <p><b>Traction Boot</b></p> <ul style="list-style-type: none"> <li>• Horizontal rotation of traction boot – 360 degree</li> <li>• Vertical rotation of traction boot – 360 degree</li> <li>• Height adjustment range of traction boot – 400mm</li> <li>• Sliding distance of traction boot – 465mm</li> <li>• Maximum Traction travel – 180 mm</li> </ul> <p><b>Transport Cart</b></p> <ul style="list-style-type: none"> <li>• Length –at least 1055mm</li> <li>• Width – at least 755mm</li> <li>• Height –at least 655mm</li> </ul> <p><b>Boot type stirrups (pair) for foot and calf support with 2 clamps.</b></p> <p><b>Gel Pad Accessories:</b></p> <ul style="list-style-type: none"> <li>• Long gel body roll large,50×15×7 – (pair) (+/-2cm)-(pair)</li> <li>• Arm/leg pad, long,50×15×4 – (pair) (+/-2cm)-(pair)</li> <li>• Universal square pad-large,50×30×1.5 (+/-2cm) (1piece)</li> </ul>				
---	--	--	--	--

- Adult horseshoe headrest with Extension
- Short gel body roll, large, 30×15×7- (+/- 2cm)-(pair)

**CERTIFICATES:**

- IEC 60601-1:2012
- IEC 60601-1-2:2014
- CE Certificate

**At least 3 Years Warranty on Parts and Labor**

**Delivery Period: 60 Days**

**Terms of Reference:**

- 1) Certified True Copy/Notarized certification of current and valid Authorized or Exclusive Distributorship.
- 2) Certified True Copy/Notarized certificate of current and valid Manufacturer's compliance with ISO 13485
- 3) Notarized certification from the manufacturer stating that the equipment is brand new, unused and not a discontinued model or was listed on the market recall.
- 4) Notarized certificate guaranteeing the availability on the supply of spare parts within ten (10) years from end of production. A certification must be issued by the manufacturer for the bidder.
- 5) Notarized certification that the bidder must be in the business in the local market for a minimum of ten (10) years.
- 6) Notarized certification that the system or machine is not a retrofit solution.
- 7) Notarized certification of manufacturer's approved US FDA Premarket Notification (PMN) or CE Mark Approval Certificate
- 8) The winning bidder shall provide current and valid calibration certificate for each equipment during delivery if deemed necessary.
- 9) Notarized certification that the supplier has the capability or authority for corrective and preventive maintenance of the unit. The

	<p>certificate must be issued by the manufacturer to the bidder.</p> <p>10) Notarized certification from the manufacturer authenticated by the Philippines consulate from the country of origin of the unit that the warranty should not be affected with a change of distributor.</p> <p>11) Notarized certificate that the bidder/supplier shall provide a three (3) years warranty for parts and services that include corrective maintenance, preventive maintenance, and/or calibration. The warranty shall commence upon the acceptance of the end user.</p> <p>12) Bidder must provide preventive maintenance and/or calibration schedule within warranty period.</p> <p>13) Certified True Copy /Notarized certification that the bidder should be ISO 9001:2015 compliant</p> <p>14) Notarized certification the supplier/bidder shall provide applications training and certification for end users and maintenance personnel of the hospital.</p> <p>15) Certified True Copy /Notarized certification to provide Manuals: two (2) sets of Service Manual in English Language and two (2) sets of User Manual in English Language upon delivery of the equipment.</p>				
<b>GRAND TOTAL</b>					<b>₱ 6,410,000.00</b>

You are hereby required to provide the following documents within ten (10) calendar days:

- Notarized Contract Agreement Form (legal size) for the Procurement of **Public Bidding for the Supply, Delivery, Installation, Testing and Commissioning of Brand-New Operating Room Table for Pavilion 7 – General Hospital CY 2024;**

***Note:*** Signatory: **NOEL V. REYES, MD, FPPA, MMHoA, Medical Center Chief II;** and

- Performance Security in any forms and amount stipulated below:

A. Cash or Cashier's / Manager's Check issued by a Universal or Commercial Bank.	Five Percent (5%) of the Total Contract Price
B. Bank draft/guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, That it shall be confirmed or authenticated by a Universal or	

Commercial Bank, if issued by a foreign bank.	
C. Surety Bond callable upon demand issued by a surety or insurance company duly certified by the Insurance Commission as authorized to issue such security.	Thirty Percent (30%) of the Total Contract Price

**NOTE: Failure to provide any of the aforementioned requirements within ten (10) calendar days shall constitute sufficient ground for cancellation of the Award and forfeiture of the Bid Security.**

Truly yours,



**NOEL V. REYES, MD, FPPA, MMHoA**  
 Medical Center Chief II *sq* *qu*

CONFORMED BY:

DATE AND TIME:

*Katrina T. Fringay*  
JAN. 17, 2018