



SUPPLEMENTAL BID BULLETIN

ADDENDUM NO. 1

PUBLIC BIDDING FOR THE SUPPLY, DELIVERY, INSTALLATION, TESTING AND COMMISSIONING OF BRAND-NEW OPERATING ROOM TABLE FOR PAVILION 7-GENERAL HOSPITAL CY 2024

This Supplemental Bid Bulletin No. 1 dated **December 04, 2024** is issued to clarify, modify or amend items in the Bid Documents. This shall form an integral part of the Bid Documents.

A. Amendments / Clarifications:

FROM	TO
<p>ON SECTION III: BID DATA SHEET / LIST OF ITEMS</p> <p>p. Notarized certification from the manufacturer authenticated by the Philippines consulate from the country of origin of the unit that the warranty should not be affected with a change of distributor.</p>	<p>ON SECTION III: BID DATA SHEET / LIST OF ITEMS</p> <p>p. Notarized certification from the manufacturer authenticated by the Philippines consulate from the country of origin of the unit that the warranty should not be affected with a change of distributor.</p> <p>➤ "Provision will be retained"</p>
<p>ON LIST OF ITEMS / TECHNICAL SPECIFICATIONS</p> <p>Under OR-01-2024: Supply, Delivery, Installation, Testing and Commissioning of Brand-New Operating Room Table for Pavilion 7 CY 2024</p> <p>OPERATING ROOM TABLE FOR VARIOUS SURGICAL DISCIPLINE WITH ORTHOPEDIC TRACTION DEVICE</p> <p>GENERAL DESCRIPTION</p> <ul style="list-style-type: none"> • Safe working load of at least 450kg guaranteeing highest safety and stability. 	<p>ON LIST OF ITEMS / TECHNICAL SPECIFICATIONS</p> <p>Under OR-01-2024: Supply, Delivery, Installation, Testing and Commissioning of Brand-New Operating Room Table for Pavilion 7 CY 2024</p> <p>OPERATING ROOM TABLE FOR VARIOUS SURGICAL DISCIPLINE WITH ORTHOPEDIC TRACTION DEVICE</p> <p>GENERAL DESCRIPTION</p> <ul style="list-style-type: none"> • Safe working load of at least 400kg, guaranteeing highest safety and stability.
<ul style="list-style-type: none"> • Equip with system that shall recognize the type of the table component and match the anti-collision data automatically. 	<ul style="list-style-type: none"> • Equip with system that shall recognize the type of the table component and match the anti-collision data automatically. <u>(Optional)</u>
<ul style="list-style-type: none"> • Equip with warning/notification indication technology to show the angle and issue a timely warning when it comes to excessive Trendelenburg and reverse Trendelenburg positions. 	<ul style="list-style-type: none"> • Equip with warning/notification <u>technology to prevent excessive angle movement in the Trendelenburg</u> and reverse Trendelenburg positions.

"There is no Health without Mental Health"

<ul style="list-style-type: none"> The table pad should be double layered and not soft but can be molded by the figure of the patient to deliver even counterforce and reduce the possibility of ulcer, and it should be water-proof and anti-static material and can be washed by water directly; each joint should be sealed by ultrasonic not glue and sewing. 	<ul style="list-style-type: none"> The table pad should be <u>thick if (single) or double layered</u> and not soft but can be molded by the figure of the patient to deliver even counterforce and reduce the possibility of ulcer, and it should be water-proof and anti-static material and can be washed by water directly; each joint should be sealed by ultrasonic not glue and sewing.
<ul style="list-style-type: none"> It shall be battery powered and electric /electro-hydraulic operating table with battery inside the table, which can work at least 50-80 operations for two weeks and the battery should be standard configuration. 	<ul style="list-style-type: none"> It shall be battery powered and <u>electric /electro-hydraulic or electro mechanical</u> operating table with battery inside the table, which can work at least 50-80 operations for two weeks and the battery should be standard configuration.
<ul style="list-style-type: none"> Equip with table positions memory that can save at least 15 positions, so the user can select the memorized positions for the specific surgery freely without complex adjustment. 	<ul style="list-style-type: none"> Equip with <u>table memory position technology or its equivalent (Optional)</u>.
<ul style="list-style-type: none"> Equip with electric-hydraulic system that includes table up and down, back up and down, turn left and right, Trendelenburg and reverse Trendelenburg, leg plate up & down, which shall be controlled by hand control panel. 	<ul style="list-style-type: none"> Equip with <u>electro-hydraulic or electro mechanical</u> system that includes table up and down, back up and down, turn left and right, Trendelenburg and reverse Trendelenburg, leg plate up & down, which shall be controlled by <u>hand control panel and/or remote control</u>.
TECHNICAL SPECIFICATION Basic Information <ul style="list-style-type: none"> Width of the table with rails at least 570 mm to 590 mm. 	TECHNICAL SPECIFICATION Basic Information <ul style="list-style-type: none"> Width of the table with rails <u>at least 570mm</u>.
Electric Function <ul style="list-style-type: none"> The lowest position at least 595 mm to 600 mm. 	Electric Function <ul style="list-style-type: none"> The lowest position <u>at 660 mm or lower</u>.
<ul style="list-style-type: none"> Tilting position for both left and right must be minimum of 26°. 	<ul style="list-style-type: none"> Tilting position for both left and right must be minimum of <u>25°</u>.
<ul style="list-style-type: none"> Trendelenburg position and Reverse Trendelenburg position must be minimum of 36°. 	<ul style="list-style-type: none"> Trendelenburg position and Reverse Trendelenburg position must be minimum of <u>30°</u>.
<ul style="list-style-type: none"> Back plate up position 75° to 90°. 	<ul style="list-style-type: none"> Back plate up position <u>at least 75°</u>.
<ul style="list-style-type: none"> Back plate down position 40° to 45°. 	<ul style="list-style-type: none"> Back plate down position <u>at least 40°</u>.
<ul style="list-style-type: none"> Leg plate down 90° to 105°. 	<ul style="list-style-type: none"> Leg plate down <u>at least 90°</u>.

Other Matters:

- A. Bid Security shall be 120 calendar days from the date of submission and opening of bids.
- B. Section VII: Technical Specifications - Please write "COMPLY" to indicate that requirements are met.
- C. *Eligibility requirements and technical proposal* should be in *one folder* and *financial proposal* in a *separate folder*, with shoelace on top instead of fastener, table of contents and index tabs in words, not numbers.

- D. Folder of Eligibility requirements and technical proposal should be placed in one envelope. And folder of Financial proposal should be in another envelope. Both envelopes shall then be placed in one mother envelope marked as **“Original Bid”**
- E. Documents should be arranged chronologically according to the checklist issued.
- F. Color code for folders and envelope: **GREEN**
- G. Typographical error must be counter signed by the authorized representative.
- H. All other provisions on the bidding documents which are not affected shall remain in effect.
- I. The deadline for **Submission and Opening of Bids** is scheduled on **December 11, 2024, 1:30 PM**, at the **BAC Conference Room**, National Center for Mental Health Compound, Mandaluyong City.
- J. Any bid submitted after the deadline for submission shall be declared **“LATE”** and shall NOT be accepted.
- K. The BAC shall open the bids immediately after the deadline for submission and receipt of bids.
- L. Bidder is required for equipment demonstration within 10 calendar days upon receipt of Notice of Eligibility.

For the information and guidance of all concerned.


JERRY C. RODRIGUEZ, MGM-ESP
Chairperson, Bids & Awards Committee CY2024
JR

